RECEIVED CENTRAL FAX CENTER

JAN 17 2005

Serial No. 10/708,938 - Davids et al. Art Unit: 3742 - Attorney Docket 10015 Response to January 12, 2005 Notice of Non-compliant Amendment

Page 2 of 7

## Amendments to the Claims:

Claim I (currently amended) A method for workpiece movement and positioning comprising the steps of:

loading the workpiece;

moving the said workpiece linearly to a predetermined location;

stopping the said linear movement of the said workpiece at the said predetermined

location:

returning the said workpiece to its original location;

and unloading the said workpiece;

and/or the optional steps of:

loading the workpiece;

constantly rotating the said workpiece when the said workpiece is moving linearly or

at the said predetermined location;

moving the workpiece linearly to a predetermined location;

stopping the linear movement of the workpiece at the predetermined location;

returning the workpiece to its original location;

Serial No. 10/708,938 – Davids et al. Art Unit: 3742 – Attorney Docket 10015 Response to January 12, 2005 Notice of Non-compliant Amendment Page 3 of 7

and unloading the workpiece;

and/or the optional steps of:

loading the workpiece;

moving the workpiece linearly to a predetermined location;

stopping the linear movement of the workpiece at the predetermined location;

not constantly rotating the said workpiece when the said workpiece is moving linearly or at

the said predetermined location and instead holding the said workpiece in a fixed

position for a predetermined period of time;

returning the workpiece to its original location;

and unloading the workpiece;

and/or the optional steps of:

loading the workpiece;

moving the workpiece linearly to a predetermined location;

stopping the linear movement of the workpiece at the predetermined location;

not constantly rotating the said workpiece when the said workpiece is moving linearly or at

the said predetermined location and instead holding the said workpiece in a fixed

position for a predetermined period of time;

lowering the said workpiece a predetermined distance;

262-629-5100

Serial No. 10/708,938 - Davids et al. Art Unit: 3742 - Attorney Docket 10015

Response to January 12, 2005 Notice of Non-compliant Amendment

Page 4 of 7

indexing the said workpiece by rotating the said workpiece a predetermined

incremental amount;

raising the said workpiece back into position;

holding the said workpiece in a fixed position for a predetermined amount of time;

and

repeating the said lowering, indexing, raising and holding steps until the workpiece

has been indexed 360 degrees or less as required by the said workpiece;

returning the workpiece to its original location;

and unloading the workpiece.

Claim 2 (previously presented) The method as set forth in claim 1 including an induction coil and quench means; the step of activating the induction coil and quench means as the

workpiece travels linearly to harden the workpiece.

Claim 3 (previously presented) The method as set forth in claim 2 including the step of

moving the workpiece back through the activated induction coil at a substantially greater

speed that the speed of the workpiece during hardening of the workpiece wherein the

workpiece is tempered.

Serial No. 10/708,938 – Davids et al. Art Unit: 3742 – Attorney Docket 10015

Response to January 12, 2005 Notice of Non-compliant Amendment

Page 5 of 7

Claim 4 (previously presented) The method as set forth in claim 1 including an induction coil and quench means; the step of activating the induction coil and quench means while the workpiece is being held in position.

Claim 5 (previously presented) The method of claim 1 including any of the means for milling, drilling, welding, assembling, stamping, marking or bending; including the step of activating the means for milling, drilling, welding, assembling, stamping, marking or bending.

Claim 6 (previously presented) A workpiece movement and positioning device, the workpiece being located on center with the movement and positioning device, the workpiece movement and positioning device comprising:

a frame for attaching the workpiece movement and positioning device;

a computer or control mechanism for turning on and off the workpiece movement and positioning device and other components and/or attachments;

an actuator consisting of a ball screw/ball spline assembly with servo motors and a lift shaft for providing the linear and rotational movement of the workpiece such that the workpiece can be caused to move linearly, linear and hold, linearly with rotation, and/or lift and index;

Serial No. 10/708,938 - Davids et al. Art Unit: 3742 - Attorney Docket 10015

Response to January 12, 2005 Notice of Non-compliant Amendment

Page 6 of 7

a means for moving the lift shaft linearly without undue bending or flexing;

a means for holding the workpiece in position on the lift shaft;

a manual safety switch to prevent the device from being operated unintentionally.

Claim 7 (previously presented) The workpiece movement and positioning device of

claim 6 further comprising shielding and drain pans to contain any quench fluid and

as a safety guard.

Claim 8 (previously presented) The workpiece movement and positioning device of

claim 7 further comprising induction hardening and quenching means wherein the

workpiece and hardening means can be operated in either a scan hardening process,

a pop up induction hardening process and/or a lift and index hardening process.

Claim 9 (previously presented) The workpiece movement and positioning device of

claim 7 further comprising other working tools controlled by the computer to

perform work in the workpiece.